

SELETTORI NON LUMINOSI – 2/3 POSIZIONI – CORPO IN TERMOPLASTICO

NON ILLUMINATED SELECTORS – 2/3 POSITIONS – THERMOPLASTIC BODY

posizioni - position		60°		120°		60°			60°			60°			conf. pack.
		0	1	0	1	1	0	2	1	0	2	1	0	2	
   parte superiori top side centrale central parte inferiore bottom side	 V01	X		X		X			X			X	X		-
	 V10		X		X			X			X	X			-
	 V01L	X		X		X	X		X	X			X	X	-
	 V10E		X		X		X	X		X	X	X			-
	 V01	X		X		X			X			X	X		-
	 V10		X		X			X			X			X	-
	 V01L	X		X		X	X		X	X		X	X		-
	 V10E		X		X		X	X	X		X			X	-
X = contatto chiuso / closed contact															
		PR-200T22N													5
		PR-201T22N													5
		PR-250T22N													5
				PR-204T22N											5
				PR-205T22N											5
				PR-254T22N											5
						PR-210T22N						PR-213T22N			5
						PR-230T22N			PR-232T22N			PR-233T22N			5
						PR-270T22N									5
		PR-300T22N													5
		PR-350T22N													5
				PR-304T22N											5
				PR-354T22N											5
						PR-310T22N			PR-312T22N			PR-313T22N			5
						PR-370T22N			PR-372T22N			PR-373T22N			5
						PR-380T22N						PR-383T22N			5
		PR-400T22N													5
		PR-450T22N													5
				PR-404T22N											5
				PR-454T22N											5
						PR-410T22N			PR-412T22N			PR-413T22N			5
						PR-470T22N			PR-472T22N			PR-473T22N			5
						PR-480T22N						PR-483T22N			5
															5

▼ Estrazione chiave / Key extraction

● Posizione di riposo / Rest position